Product data sheet

HELIOS 360 MO 4K SENS PIR
E7027081
CARDI



IP 44 IK 06

Plafond IP44 för inomhusbruk. Stomme av vitlackerad stålplåt. Kupa av opal akryl med vridfastsättning. LED-plattan är utbytbar. Monteras dikt tak. 2st kabelinföringar Ø 20 mm på baksidan. Förberedd för utanpåliggande kabel, 2st knock-out Ø 13 mm. Instickssplint 4x2x2,5 mm². Möjlighet till dos-montage. PIR-sensorn har ställbar efterlystid 5 sek- 8 minuter och detekteringsområdet är ställbart i två lägen med olika känslighet. Armaturen kan slava upp till 5 armaturer eller potentialfri brytkontakt. Den totala effekten bör inte överstiga 150W. Rekommenderad montagehöjd tak 2,2-4m, vägg 1,8-2,5m.

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	19 W	CRI	80
Total flux	2030 lm	LOR	100%
Luminous efficacy	107 lm/W	ULOR	7%
		Total power	19 W

Mounting mode

Ceiling mounted

Shape and measurements

Length: 14.09 in
Width: 14.09 in
Height: 2.83 in

Adjustability

Fixed

Electric

System power: 19 W
Appliance Class: I

Integrated sensors

Integrated sensors: Daylight sensor, Presence sensor

Protection

IP: 44
IK: 06