Product data sheet

VOYAGER C LED ROUTE KIT E3TX 96548981

THORN LIGHTING






CE

High performance, 3 hour SelfTest or Addressable Test if connected to Explorer Project/Vision, emergency lighting kit for incorporation into a suitable housing (not supplied). $1 \times 3W$ LED with escape route optic. Electrical connection via $1 \times 5 \times 1.5$ mm² terminals. Gear and NiMH batteries connect via plugs and sockets. Suitable for mounting up to 7m. Can be operated in either maintained, switched maintained or non-maintained modes. Total power: 5.4 W Dimensions: Module: $140 \times 30 \times 22 \text{ mm}$ Battery: $61 \times 45 \times 22 \text{ mm}$ LED Assembly: $60 \times 40 \times 44 \text{ mm}$ Weight: 0.5 kg

Light output 1 (emergency)




1 x LED

Nominal lamp power	3 W
Lamp flux	115 lm
Luminous efficacy	18 lm/W
CCT	3000 K
CRI	99

LOR Total flux Total power 84% 97 lm 5.41 W

Light output 2



1 x LED

Nominal lamp power	3 W
Lamp flux	115 lm
Luminous efficacy	18 lm/W
CCT	3000 K
CRI	99

LOR 84% Total flux 97 lm

Total power 5.41 W

Mounting mode

Ceiling recessed

Shape and measurements

Length: 2.44 in Width: 1.61 in Height: 1.77 in Weight: 0.5 kg Electric

System power: 10.82 W Voltage: 230-240 V AC

Information regarding emergency functions

Supplementary emergency lighting

Emergency sign: N/A

Protection

Designation labels: CE

Design

Material impression: Aluminum Color of housing: White