
Product data sheet


X-LINE SLIM UP&DOWN LED 2600/2600 PC/PLX EDD 21 840 LINE-1EP / L-1132MM S-1,5M
19.4415.2823.21
LUXIONA



IP 40 IK 04

Indoor luminaire. Assembly: surface mounted on slings. The body material is aluminum. Colour - RAL 9006 (grey). Dimensions: 1132 x 48 x 70 mm. Diffuser: PC/PLX (opalescent polycarbonate/PMMA opal) [up/down]. The efficiency of the optical system is 66,78%. Beam angle: (C0-C180) / (C90-C270) - 96,4° / 90,2°. Light source type: LED. Colour of the light 4000 K. SDCM=3. CRI>80. Lifetime of LED sources: 100000 h L80/B10. Luminaire luminous flux: 3580,5 lm. Power of luminaire: 28,2 W. Luminaire's light efficiency: 127 lm/W. Driver: DIM DALI (EDD). Voltage 220..240 V, 50..60 Hz. Power factor cosφ: >0,95. Circuit load capacity: 17 (B10), 28 (B16), 26 (C10), 41 (C16). Operating temperature range: 5 ÷ 35° C. Protection degree: IP40. Impact resistant: IK04. Protection against electric shock: I. Photobiological risk class (IEC/EN 62471): RG0. Geometric lines of rectangular type must be consulted with luminaire's constructor. The luminaire can be made in CLO (Constant Lumen Output) version. Please check in the data sheet and installation instructions whether installation accessories are required. *Selected luminary variants are available with ENEC certificate.

Light output 1



1 x LED

Nominal lamp power	28.2 W	LOR	52%
Lamp flux	5344 lm	Total flux	2802 lm
Luminous efficacy	190 lm/W	Total power	28.2 W
CCT	4000 K		
CRI	80		

Mounting mode

Pendant

Shape and measurements

Length: 44.57 in
Width: 1.89 in
Height: 2.76 in

Adjustability

Fixed

Design

Color of housing: Silver gray

Electric

System power: 28.2 W
Controller: DALI
Appliance Class: I

Protection

IP: 40
IK: 04

Other operating numbers

Ambient temperature range: 41...95°F