Product data sheet

TX-MOVE
901739.002
RZB



IP 20 IK 03

Series: TX-MOVE Einlege/Einbau-Flächenstrahler. Housing: aluminium, powder-coated. 2xSwivel range: 90°. High-efficiency LED units with flush-mounted opal diffuser made of non-yellowing PMMA. Symmetrical wide beam light emission. Suitable for laying in grid ceiling module 625. Connected converter included in separate gearbox. Suitable for through-wiring. MultiLumen: Luminous flux variable in 3 steps. Accessories: Mounting frame for installation in suspended ceilings. Replaceable components make repairs possible and extend the service life. Colour: traffic white, matt (RAL 9016) Length: 622 mm Width: 190 mm Height: 39 mm Cut-out length: 602 mm Cut-out width: 174 mm Recess height: 100 mm Lamp: LED Socket: without socket Colour temperature: 3000K Colour rendering index (CRI): 80 System power: 35 W Rated luminous flux: 4850 lm Beam angle Down: 112° Luminous efficiency: 139 lm/W System power 2: 47 W Rated luminous flux 2: 6250 lm Luminous efficiency 2: 133 lm/W System power 3: 68 W Rated luminous flux 3: 8450 lm Luminous efficiency 3: 124 lm/W Control gear: Regulated power supply Protection class: I Type of protection: IP 20

Light output 1



1 x LED

Nominal lamp power	17.5 W	LOR	67%
Lamp flux	2425 lm	ULOR	14%
Luminous efficacy	92 lm/W	Total flux	1618 lm
CCT	3000 K	Total power	17.5 W
CRI	80		



1 x LED

Nominal lamp power	34 W	LOR	67%
Lamp flux	4225 lm	ULOR	14%
Luminous efficacy	83 lm/W	Total flux	2818 lm
CCT	3000 K	Total power	34 W
CRI	80		



1 x LED

Nominal lamp power	23.5 W	LOR	67%
Lamp flux	3125 lm	ULOR	14%
Luminous efficacy	89 lm/W	Total flux	2085 lm
CCT	3000 K	Total power	23.5 W
CRI	80		

Light output 2



1 x LED

Nominal lamp power	34 W	LOR	67%
Lamp flux	4225 lm	ULOR	14%
Luminous efficacy	83 lm/W	Total flux	2818 lm
CCT	3000 K	Total power	34 W
CRI	80		



1 x LED

Nominal lamp power	23.5 W	LOR	67%
Lamp flux	3125 lm	ULOR	14%
Luminous efficacy	89 lm/W	Total flux	2085 lm
CCT	3000 K	Total power	23.5 W
CRI	80		



1 x LED

Nominal lamp power	17.5 W	LOR	67%
Lamp flux	2425 lm	ULOR	14%
Luminous efficacy	92 lm/W	Total flux	1618 lm
CCT	3000 K	Total power	17.5 W
CRI	80		

Mounting mode

Ceiling recessed

Shape and measurements

Length: 7.48 in
Width: 24.49 in
Height: 1.54 in

Adjustability

Rotatable, Tiltable

Design

Color of housing: White

Electric

System power: 35-68 W

Protection

IP: 20
IK: 03