


# Product data sheet

CIRCULAR INWARD Ø3000 RECESSED  
CD5D-00V9AZRU05  
LEDSC4



LedsC4 Circular Inward ø3000 Recessed CD5D-00V9AZRU05V1 Pendant for indoor use. For uplighting and downlighting. Structure finish: Black. Diffuser material: Polycarbonate. Diffuser finish: Opal. Warranty: 5 Years. Product net weight (Kg): 18 Product width or diameter (mm): 3030 Product height (mm): 5000 Ø of the hole for recessing (mm): 100 Class 1. IP: IP20. LED. No. of lampholders or LEDs: 1. Driver brand: MEANWELL. Maximum power of light source: 180.8W. Colour temperature: 2700K. Colour rendering index: 90. MacAdam Steps: 3. Hours of life: 50.000h L80B20. UGR: 4.2. Photobiological risk: RG1. Real flux (lm): 9391. Real lm/W: 49. Voltage / frequency range: 100-305/50-60Hz. Voltage: 2,8. Equipment included: Yes. Total power: 190. Power factor: 0.90. Dimmable equipment included: 0-10V.

## Light output 1



1 x LED			
Nominal lamp power	190 W	LOR	100%
Lamp flux	9391 lm	ULOR	50%
Luminous efficacy	49 lm/W	Total flux	9391 lm
CCT	2700 K	Total power	190 W
CRI	90		

## Mounting mode

Pendant, Table luminaire

## Shape and measurements

Length: 118.11 in  
Width: 118.11 in  
Height: 1.18 in

## Adjustability

Fixed

## Electric

System power: 190 W  
Appliance Class: I

## Protection

IP: 20