

Product data sheet


MODRC L35
MOD CURVE
DEXTRA



IP
20

MOD Curve - 600x600 Recessed lay-in luminaire, white powder coated one piece steel body, Aluminium framed front panel. Curved polycarbonate diffuser. Options: E3 - Emergency control gear (407 lumens output) ST3 - Emergency Selftest AT3 - Emergency Autotest S - Switch Dimming D - Digital Dimming (DSI) A - Digital Addressable Lighting Interface (DALI) C - Bi-Level Dimming (Corridor Function) H - High Frequency Dimming (Analogue 1-10v) 4PM - 4 Pole panel mount 6PM - 6 Pole panel mount C83 - CRI 80, 3000K IP44 - IP44 (from below) MODRS TETHER KIT - Secondary fix single drop MODRS TETHER KIT TWIN- Secondary fix twin drop

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	21.6 W	CRI	80
Total flux	2723 lm	LOR	100%
Luminous efficacy	126 lm/W	ULOR	4%
		Total power	21.6 W

Mounting mode

Ceiling recessed

Shape and measurements

Length: 23.43 in
Width: 23.43 in
Height: 6.69 in

Adjustability

Fixed

Electric

System power: 21.6 W

Protection

IP: 20