



# Product data sheet

PURA SPOT S MIDI  
741785.002  
RZB



Series: Pura Spot S Type of Protection: IP 20 Protection Class: I Voltage: 220 - 240 V / 50 - 60 Hz Housing: powder coated die cast aluminium, rotates 356° horizontally and swivels 180° vertically, heat resistant plastic ring. Reflector: faceted aluminium, included, can be changed without tools, passive cooling, with multi adapter for 3 circuit tracks. LED included. Available Colours: Traffic white, matt (RAL 9016) Type of Installation: Track on ceiling Dimensions: L 194, B 134, H 133 Lamp: LED Life time: 50000 h (L90/B10) Colour Temperature: 3100K Socket 1: without socket Operating Mode Lamp 1: Regulated power supply Safety Marks: F-mark Impact Protection: IK03 (0,35 Joule) Luminaire flux LED: 1650lm System power: 20W Beam Angle: 38° Number of fittings B10A: 15 Number of fittings B16A: 25 Inrush current: 16A Unified Glare Ratio: 17,9 EEC: A+

## Light output 1 (integrated)



|                    |         |             |        |
|--------------------|---------|-------------|--------|
| Lamp type          | LED     | CCT         | 3100 K |
| Nominal lamp power | 20 W    | CRI         | 90     |
| Total flux         | 1650 lm | LOR         | 100%   |
| Luminous efficacy  | 82 lm/W | Total power | 20 W   |

## Mounting mode

Ceiling mounted

## Shape and measurements

Length: 5.28 in  
Width: 7.64 in  
Height: 5.28 in

## Adjustability

Rotatable, Tilttable

## Design

Color of housing: White

## Electric

System power: 20 W

## Protection

IP: 20  
IK: 03