
Product data sheet

47 CAMINO LED OUTDOOR LIGHT FITTING
47 6403A 518 (47000 0445)
SCHUCH



LED outdoor light fitting, CAMINO, 140 W, 12740 lm, 91 lm/W, Class II, IP66, asymmetrical beam, 1800 K, CRI≥ 50, Ta -40 °C/+25 °C, L90>100000 h (@ Ta max), Pane Safety glass clear, Housing Die-cast aluminium, Colour grey, DB702N. LED outdoor light fitting of the GreenLine series with outstanding sustainable product design. Consisting of powder-coated die-cast aluminium housing, two-part. Upper part with ECG, LED modules, optics and frameless tempered safety glass pane, hinged and detachable from the lower part. Lower part with integrated pole mounting system, adjustable inclination, cable entry, strain relief and integrated pressure compensation system (dirt-resistant). Electro kit carrying all electrical components, completely removable by unplugging isolating plug connection. Zhaga LED modules with highly efficient optics, direct beam, Multi-Layer Technology. ECG with high surge protection, overload and short circuit protection. Universal die-cast aluminium pole mounting system for pole-top Ø 60/76mm and side-entry mounting Ø 42/60mm. Resource-saving and environmentally friendly thanks to interchangeability of components (no disposable light fitting). Length 685,00 mm, Width/Diameter 322,00 mm, Height 154,00 mm, Net weight 10,30 kg.

Light output 1 (integrated)



Lamp type	LED	CCT	1800 K
Nominal lamp power	140 W	CRI	50
Total flux	12740 lm	LOR	100%
Luminous efficacy	91 lm/W	ULOR	7%
		Total power	140 W

Mounting mode

Pole top mounted, Pole integrated

Shape and measurements

Length: 26.97 in
Width: 12.68 in
Height: 6.06 in

Adjustability

Fixed

Electric

System power: 140 W
Appliance Class: I

Protection

IP: 66
IK: 09
Designation labels: CE, ENEC