



# Product data sheet

INTO R160 LED DALI 30W 22° 3350LM 3000K IP20 WHITE  
030561.3L03.321  
LUG



Decorative downlight luminaire, adapted for tool-free assembly, for suspended ceilings, for LED light sources. The luminaire in round version with different angles of light distribution. Mounting: in the ceiling, with mounting brackets (included) Body: aluminum Power: 220-240V 50/60Hz Includes light source: yes Lifetime (L80B10): 60 000 h Warranty: 5 years Application: public utility facilities, delicatessen, supermarkets, shopping centers, offices, car showrooms, pathways, halls, classrooms, corridors, flats

## Light output 1 (integrated)



|                    |          |             |        |
|--------------------|----------|-------------|--------|
| Lamp type          | LED      | CCT         | 3000 K |
| Nominal lamp power | 30 W     | CRI         | 80     |
| Total flux         | 3350 lm  | LOR         | 100%   |
| Luminous efficacy  | 112 lm/W | Total power | 30 W   |

## Mounting mode

Ceiling recessed

## Shape and measurements

Height: 3.46 in

Diameter: 6.30 in

## Adjustability

Fixed

## Design

Color of housing: White

## Electric

System power: 30 W

Controller: DALI

Appliance Class: II

## Protection

IP: 20