

Product data sheet


LEDSPOTRA-HQII 9W-DIM-4000-36D-WH-GP
541003056110
OPPLE



IP
20

Housing: Aluminium Alloy; Mounting ring: white Installation: recessed; Dimensions: 62*Φ86; Ceiling cutouts: φ70; Power: 9W; Efficacy : 67Lm/w Colour temperature: 4000K; Colour rendering: RA80 Total luminous flux of luminaire: 600Lm Beam angle: 36°; Glare control: UGR<19; Service life: 30,000h at 70% luminous flux; Degree of protection: IP20; Class of protection II; Mains voltage: 220-240V/50-60Hz; Remark : Accessory Lens provide: honeycomb HQII-GP, filter-blue-light HQII-GP, filter- red-light HQII-GP, filter-ylw-light HQII- GP, lens-ellipse HQII-GP

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	9 W	CRI	80
Total flux	600 lm	LOR	100%
Luminous efficacy	67 lm/W	Total power	9 W

Mounting mode

Ceiling recessed

Shape and measurements

Length: 3.39 in
Width: 3.39 in
Height: 2.44 in

Adjustability

Free

Electric

System power: 9 W

Protection

IP: 20