


Product data sheet

MULTILUME SLIM DELTA VTB 300X600 840 ENSTO CLO
23167-520
FAGERHULT



Installation Recessed mounting in suspended ceilings. Unventilated or ventilated ceilings. For suspended ceilings with visible T-bars (15 or 24 mm). Do not cover with insulation. For detailed information, see the installation instructions on our website. Connection Connection in separate ballast box.Snap-in terminal block 3x2,5mm2 (x2), through-wiring possible. 5x2,5mm2 (x2) when dimming. Can also be supplied with earthed mains cable and plug. Design Luminaire body of white enamelled sheet steel (RAL 9016). Louvre Delta – microprism louvre in UV stabil polystyrene. Miscellaneous Enclosure class IP 44 under suspended ceilings and IP 20 above suspended ceilings.

Light output 1 (integrated)



| | | | |
|--------------------|----------|-------------|--------|
| Lamp type | LED | CCT | 4000 K |
| Nominal lamp power | 20 W | CRI | 80 |
| Total flux | 2112 lm | LOR | 100% |
| Luminous efficacy | 106 lm/W | Total power | 20 W |

Mounting mode

Ceiling recessed

Shape and measurements

Length: 23.43 in
Width: 11.61 in
Height: 0.91 in

Adjustability

Fixed

Design

Color of housing: White

Electric

System power: 20 W

Protection

IP: 44