


Product data sheet

MONSUN 2X49W T5 HF PMMA IP65
3377516
SOLAR




Monsun er konstruert for å tåle hard belastning i tøffe miljøer. Armaturhusene til Monsun er av glassfiberarmert polyester. Flammebestandig og motstandsdyktig i aggressive miljøer. Bruksområde: Dette er armaturer som egner seg godt til belysning av industrilokaler. Ellers er egnede bruksområder parkeringshus, tilfluktsrom, låver, verksteder osv. Montasje: Monsun monteres direkte i tak, på wire, i kjetting eller i DUS-skinne. Tilkobling: Armaturen leveres med konvensjonell reaktor eller elektronisk forkoblingsutstyr. T5 armaturene med elektronisk forkobling. Armaturene kan leveres med dimbart elektronisk forkoblingsutstyr. 3 polet tilkoblingsklemme for max 2,5 mm². Isolasjonsklasse I Kapsling: IP65


Light output 1



2 x T8			
Nominal lamp power	58 W	LOR	61%
Lamp flux	5200 lm	ULOR	8%
Luminous efficacy	55 lm/W	Total flux	6364 lm
CCT	3000 K	Total power	116 W
CRI	80		



2 x Fluorescent lamp tubular T5			
Nominal lamp power	49 W	Socket	G5
Lamp flux	4300 lm	LOR	61%
Luminous efficacy	45 lm/W	ULOR	8%
CCT	4000 K	Total flux	5262 lm
CRI	85	Total power	116 W



2 x Fluorescent lamp tubular T5			
Nominal lamp power	49 W	Socket	G5
Lamp flux	4300 lm	LOR	61%
Luminous efficacy	45 lm/W	ULOR	8%
CCT	3000 K	Total flux	5262 lm
CRI	85	Total power	116 W

Mounting mode

Ceiling mounted

Shape and measurements

Length: 62.09 in

Width: 5.12 in

Height: 4.17 in

Electric

System power: 116 W

Protection

IP: 65