Product data sheet

LIGHT LINEAR PT 1 BOLLARDS
LI-10021-T4-8040
LIGMAN



IP 65 IK 10

- Lamp LED - CRI Ra > 80 - MacAdam Ellipse 3 SDCM - Colour 2700K,3000K and 4000K - Die-cast aluminium housing - Extruded aluminium column - Pre-treated before powder coating ensuring high corrosion resistance - Single cable entry - One IP68 connector supplied with 0.2 m of 3x1.0 sqmm outdoor cable - Stainless steel fasteners in grade 304 with zinc flake coating (ZFC) - Durable silicone rubber gasket - Clear toughened glass - High-efficiency PMMA lens - Integral control gea

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	26.5 W	CRI	80
Total flux	3057 lm	LOR	100%
Luminous efficacy	115 lm/W	Total power	26.5 W

Mounting mode

Standing / Bollard

Shape and measurements

Length: 11.89 in
Width: 7.87 in
Height: 39.37 in
Weight: 11.2 kg

Adjustability

Fixed

Electric

System power: 26.5 W
Ballast: ECG
Controller: Dimmable 1..10V, DALI
Appliance Class: I

Protection

IP: 65
IK: 10
Surface temperature: 40°C