
Product data sheet


HALO SUSP. DI/ID BLACK 450MM
R48H045-9005E2940H3S
PLANLICHT



IP 40


LED LO 4000K CRI>90 26W 1874lm https://katalog.planlicht.com/en-gb/fam-halo/

Light output 1 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	7.75 W	CRI	90
Total flux	522 lm	LOR	100%
Luminous efficacy	67 lm/W	Total power	7.75 W

Light output 2 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	7.75 W	CRI	90
Total flux	522 lm	LOR	100%
Luminous efficacy	67 lm/W	Total power	7.75 W

Light output 3 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	7.75 W	CRI	90
Total flux	522 lm	LOR	100%
Luminous efficacy	67 lm/W	Total power	7.75 W

Light output 4 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	7.75 W	CRI	90
Total flux	522 lm	LOR	100%
Luminous efficacy	67 lm/W	Total power	7.75 W

Light output 5 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	7.75 W	CRI	90
Total flux	522 lm	LOR	100%
Luminous efficacy	67 lm/W	Total power	7.75 W

Light output 6 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	7.75 W	CRI	90
Total flux	522 lm	LOR	100%
Luminous efficacy	67 lm/W	Total power	7.75 W

Mounting mode

Pendant

Shape and measurements

Length: 17.72 in

Width: 17.72 in

Height: 2.48 in

Adjustability

Fixed

Electric

System power: 46.5 W

Protection

IP: 40

Designation labels: CE