


# Product data sheet

CONE 3 - POLE TOP LIGHT  
7211-0-3-752-XX  
UNILAMP




Description CONE is as its name suggests, a series of cone-shaped pole top and wall mounted luminaires with shielded light source. The recommended mounting height is between 3 – 4 metres. CONE2 is assembled with a glare suppression opal polymer which gives a wide light distribution. To avoid discolouration of the lens we have used a high quality PMMA clear cover. Recommended uses are in gardens, parks, residential areas, squares and public spaces. Aluminium pole, galvanized steel pole and anchor unit for concrete foundation are also available. Specification • Designed, Manufactured and Tested according to IEC 60598-1, IEC 60598-2-1 and VDE regulations. • LM6 Die-Cast Aluminium, Cast Aluminium alloy and Extruded Aluminium body. • Stainless steel screws. • Nano Ceramic surface conversion. • Double layer coating. • PMMA cover. • Post-cured silicone gasket. • High quality LED module and driver. • GFR PA6.6 Terminal block. • Weather proof grommet(Wall Light) or M20 cable gland(Pole Light). • Pole light pre-wired with outdoor cable. • Installation work has to be carried on according to the enclosed product manual.

## Light output 1



1 x Metal halide lamp			
Nominal lamp power	70 W	Socket	G12
Lamp flux	6600 lm	LOR	73%
Luminous efficacy	94 lm/W	ULOR	3%
CCT	4000 K	Total flux	4819 lm
CRI	94	Total power	83 W



1 x Metal halide lamp			
Nominal lamp power	70 W	Socket	G12
Lamp flux	6600 lm	LOR	73%
Luminous efficacy	94 lm/W	ULOR	3%
CCT	3000 K	Total flux	4819 lm
CRI	88	Total power	83 W

## Mounting mode

Pole top mounted

## Shape and measurements

Length: 15.03 in  
Width: 15.03 in  
Height: 25.35 in

## Electric

System power: 83 W  
Appliance Class: I

## Protection

IP: 54  
IK: 07

Adjustability

Fixed