



Product data sheet

SRT-SYSTEM IP20-SRGVCXT PP/2250 LED - GERÄTETRÄGER VARIABLE CENTRAL.LINE.OPTIC | DEVICE MOUNT VARIABLE...
21000 865 ET VW RAL 9016 (SRT+19545024270)
REGIOLUX



SRT-Quick-fit mounting system, Variable device mount, Modullänge/2250. Device mount made of a galvanised, profiled steel sheet; surface coated with polyester resin. Tool-free attachment with design-integrated pressure caps guarantee protection against theft and dismantling. Variable position on the mounting rail. Housing colour traffic white RAL 9016. Performance level: Powerful Performance (PP) - Powerful, universal all-rounder, sets very high standards for efficiency, service life and warranty period, Light distribution direct, extra narrow distribution by means of Central.Line.Optic of PMMA plastic, The lens optics ensure ease of installation and are easy to maintain thanks to the easy-to-clean surface. The density of the single-row lens arrangement ensures that the points merge into a line with a homogeneous appearance in the object. The light source and driver are removable in accordance with the EU 2019/2020 ecodesign requirements and can be replaced in the factory. Electrical connection by means of a 1m connection cable for variable device mount positioning with a 3-pin, quick-fit plug connector in the light run with free phase pre-selection. They are exchangeable, permit modernisation and reliably prolong the service life of the overall system. Dimensions (LxWxH): 2299mm x 55mm x 37mm Beam angle: 25°(C0)/55° (C90) Placement: LED, Colour rendering/Light colour CRI ≥ 80 / 6500K Colour tolerance: 3SDCM Photobiological safety (Luminaire): RG1 LED service life: 75000h L80/B10 (Tq 30°C), 100000h L80/B50 (Tq 30°C) Nominal luminous flux: 20669lm Luminaire luminous efficiency: 157lm/W Control gear: Electronic driver (1 pcs.) System output: 132W Energy efficiency class/light source: B Mains voltage: 230V Mains frequency: 50Hz Impact resistance (IK rating): IK03 (-20°C bis 30°C) Ambient temperatur: ta -20°C to 30°C UGR lat./long.: 16.3 / 20.9 Certification mark: IP20, Protection class I, ENEC10 VDE, F, HACCP DIN10500/Food/IFS-application-related suitability (see certificate)/BRC, Indoor, CE Warranty period: 7 years Regiolux GmbH Type: SRGVCXT PP /2250 LED 21000 865 ET vw RAL 9016 Article number: 19545024270 Product deep link: <https://www.regiolux.de/en/article/19545024270> General warranty conditions: www.regiolux.de/en/Service/Warranty

Light output 1 (integrated)



Lamp type		CCT	6500 K
Nominal lamp power	131.7 W	CRI	80
Total flux	20669 lm	LOR	100%
Luminous efficacy	157 lm/W	Total power	131.7 W

Mounting mode

Ceiling mounted, Contact rail

Shape and measurements

Length: 90.63 in
Width: 2.48 in
Height: 2.64 in

Electric

System power: 131.7 W
Appliance Class: 0

Protection

IP: 20
IK: 03
Designation labels: CE, ENEC

Design

Color of housing: White