


Product data sheet

3F LINDA INOX 1X36 HF
5221
3F FILIPPI



ILLUMINOTECHNICAL Luminous efficiency >78% (lower >66%, upper >12%). Diffused symmetric distribution. UGR <21 (EN 12464-1).
MECHANICAL Self-extinguishing V2 polycarbonate housing, injection moulded, RAL 7035 grey. Ecologic anti-aging injected sealing gasket. Diffuser in self-extinguishing V2 polycarbonate, photo-engraved interior, UV stabilised, injection moulded with smooth outer surface, tamper-proof opening. Gear-holder reflector in hot-dip galvanised steel, painted with white polyester base. Snug fit safety snap-lock clips for diffuser mounting in stainless steel, screwdriver opening. Dimensions: 100x1270 mm, height 100 mm. Weight 2.05 kg. IP66 protection degree. Luminaire with limited surface temperature. - D - Mechanical strength 6.5 joule. Glow-wire test resistance 850°C. ELECTRICAL EEI A2 electronic wiring, 230V-50/60Hz, power factor >0.95, lamp warm start, constant output power, class I. ENEC. SUPPLIED Fixing brackets in stainless steel. APPLICATIONS Dry, dusty indoor environments, subject to occasional water splashes. Virtually in all environments compatibly with the emissions/atmospheres compromising the use of plastic materials. Not suitable for installation on surfaces subject to important vibrations, exposed to weather conditions, on ropes or poles.

Light output 1



1 x Fluorescent lamp tubular T8			
Nominal lamp power	36 W	Socket	G13
Lamp flux	3350 lm	LOR	78%
Luminous efficacy	73 lm/W	ULOR	12%
CCT	4000 K	Total flux	2614 lm
CRI	80	Total power	36 W

Mounting mode

Ceiling mounted

Shape and measurements

Length: 50.00 in
Width: 3.94 in
Height: 3.94 in

Adjustability

Fixed

Design

Color of housing: Silver gray

Electric

System power: 36 W
Appliance Class: I

Protection

IP: 66