Product data sheet


FIL45 SUR 1680 3900 840 OPAL DALI GR.
F41SF168MOOP840DG
LAMP



IP 20 IK 07

Suspended or mounted surface structure model FIL45 SUR 1680 LAMP brand. Made in extruded recycled aluminum with a rate of 80%, with opal polycarbonate diffuser. Model for LED MID-POWER, colour temperature 4000K with CRI80 and with electronic wiring Dali included. With IP43, except for suspended installation, which becomes IP20, IK07 protection rating. Insulation Class I. Photobiological safety group 0. LED life time: 70.000 L80 B10. Available finishes: White, black and grey. Environmental Product Declaration - EPD®available, according to UNE-EN ISO 9001:2015 and UNE-EN ISO 14001:2015.

Light output 1



1 x LED

Nominal lamp power	26 W	LOR	100%
Lamp flux	3056 lm	Total flux	3051 lm
Luminous efficacy	118 lm/W	Total power	26 W
CCT	4000 K		
CRI	80		

Mounting mode

Ceiling mounted

Shape and measurements

Length: 66.14 in
Width: 1.77 in
Height: 3.15 in

Adjustability

Fixed

Electric

System power: 26 W
Appliance Class: I

Protection

IP: 20
IK: 07