
Product data sheet

FORREY 26 PENDANT LUMINAIRES
FOR-95002-T2-W40
LIGMAN



- Lamp COB - CRI Ra > 80 - MacAdam Ellipse 3 SDCM - Colour 3000K , 4000K - Die-cast aluminium housing and frame pre-treated before powder coating ensuring high corrosion resistance - Two cable entries for through wiring - Stainless steel fasteners in grade 316 - Durable silicone rubber gasket - Opal, impact-resistant, UV-stabilised polycarbonate diffuser - Downward light distribution type without external optical lenses - Models with shade will have colour white coating at inside of shade luminaire and outside surface coating according to colour of luminaire - Integral control gear

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	47.7 W	CRI	80
Total flux	3737 lm	LOR	100%
Luminous efficacy	78 lm/W	ULOR	100%
		Total power	47.7 W

Mounting mode

Ceiling mounted, Wall recessed

Shape and measurements

Height: 41.14 in
Diameter: 25.98 in
Weight: 4.5 kg

Adjustability

Free

Design

Color of housing: Black, White, Silver gray

Glare protection

Glare protection: UGR < 19

Electric

System power: 47.7 W
Ballast: ECG
Controller: Dimmable 1..10V, DALI
Appliance Class: I

Protection

IP: 65
IK: 08
Surface temperature: 40°C
Designation labels: CE, UL