Product data sheet


HELEDON MAXI E
901760.004.1
RZB



IP 20 IK 06

Series: HELEDON maxi Round recessed downlight. Housing made of die-cast aluminium, powder-coated. Black plastic ring and recessed LED to prevent glare from the side. Optical assembly with lens made of plastic (polycarbonate) for the best homogeneous light distribution - can be changed without tools. Best colour rendering index Ra>90. Suitable for Recessed ceiling mounting. Installation without tools thanks to spring fastening system. Separate LED converter with connecting cable 600 mm. High quality converter without flickering and stroboscopic effect. Through-wiring box (5 pole) available as accessory. The following accessories can be mounted without use of tools: interchangeable lenses, decorative glasses, honeycomb louvre, clear and frosted diffusers, white interchangeable plastic ring. Colour: silver Diameter: 162 mm Height: 3 mm Cut-out diameter: 152 mm Recess height: 200 mm Luminaire: recess height: 135 mm Lamp: LED Socket: without socket Colour temperature: 4000K Colour rendering index (CRI): 92 System power: 25 W Rated luminous flux: 3000 lm Beam angle Down: 13° Luminous efficiency: 120 lm/W Control gear: Regulated power supply Protection class: II Type of protection: IP 20

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	25 W	CRI	90
Total flux	3000 lm	LOR	100%
Luminous efficacy	120 lm/W	ULOR	13%
		Total power	25 W

Mounting mode

Ceiling recessed

Shape and measurements

Height: 0.12 in
Diameter: 6.38 in

Adjustability

Fixed

Electric

System power: 25 W

Protection

IP: 20
IK: 06