

Product data sheet


HLB4 LED 4" MICROEDGE™ DIRECT MOUNT DOWNLIGHT
HLB406930
COOPER LIGHTING



IP
47

Ultra-thin round lens downlight with remote driver/junction box, Install into drywall/suspended ceilings (no J-box or housing required), Install from below the ceiling in as little as a 1-1/2" plenum height, 5 selectable color temperatures: 2700K, 3000K, 3500K, 4000K, 5000K CCT, CRI: 90; L70 at 50,000 hours (70% lumen maintenance at 50,000 hours), Wet location listed for showers and protected ceilings, For Insulated Ceiling (IC) rated and Non-IC rated applications, 120V; Phase dimming down to 5%; Lumens: up to 750, AIR-TITE™ reduces airflow between unconditioned and conditioned spaces, ENERGY STAR™ certified; 5-year warranty

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	12 W	CRI	90
Total flux	723 lm	LOR	100%
Luminous efficacy	60 lm/W	Total power	12 W

Mounting mode

Ceiling recessed

Shape and measurements

Height: 0.39 in
Diameter: 4.01 in

Adjustability

Fixed

Electric

System power: 12 W

Protection

IP: 47