Product data sheet


LIGHTING FOR ADMINISTRATIVE AND OFFICE BUILDINGS
V1-A0-00070-01OPS-4003065 A070 2.0 IP40 595X595X50 MM 30W 6500K OPAL MICROWAVE SENSOR
VARTON



IP 40 IK 03

Versatile office luminaire. Stainless steel housing with white powder coating. Application:administrative facilities, lobbies.Recessed and surface-mounted. Compatible with the Armstrong Prelude 24 suspended ceiling systems. Input voltage (AC, 50Hz), V: 176...264 AC frequency, Hz: 50 Flicker, %: 2 Climatic modification and category of placement: УХЛ4 Height/depth, mm: 50 Length, mm: 595 Protection class: I Ingress protection (IP): IP40 Impact resistance: IK03 Width, mm: 595 Power factor: 0,95 https://www.varton.ru/products/ofisnoe-osveshchenie/a-seriya-2-0/a070-2-0-ip40-ofis-595-595-analog-4-18/svetodiodnyy-svetilnik-varton-a070-2-0-ofisnyy-30-vt-vstraivaemyy-nakladnoy-6500-k-595kh595kh50-mm-i_7/

Light output 1



1 x LED

Nominal lamp power	30 W	LOR	100%
Lamp flux	3840 lm	Total flux	3840 lm
Luminous efficacy	128 lm/W	Total power	30 W
CCT	6500 K		
CRI	80		

Mounting mode

Ceiling recessed

Shape and measurements

Length: 23.43 in
Width: 23.43 in
Height: 1.97 in

Adjustability

Fixed

Electric

System power: 30 W

Protection

IP: 40
IK: 03