Product data sheet

OFFICE LUMINAIRES FOR SPECIAL CEILINGS

V1-A5-00402-10000-2003040 ROCKFON X 600X600 MM 30W 4000K OPAL


VARTON



IP 40 IK 02

Luminaire for Rockfon ceiling system with egde X . Stainless steel housing with white powder coating. Application: administrative facilities, lobbies Recessed mounted compatible with Rockfon X. Input voltage (AC, 50Hz), V: 176...264 AC frequency, Hz: 50 Flicker, %: 1 Climatic modification and category of placement: УХЛ4 Protection class: I Ingress protection (IP): IP40 Impact resistance: IK02 https://www.varton.ru/products/ofisnye-svetilniki-dlya-nestandartnykh-potolkov/varton-dlya-rockfon/rockfon-x-600x600-mm/svetodiodnyy-svetilnik-varton-dlya-potolkov-rockfon-c-kromkoy-x-600kh600kh70-mm-30vt-4000-k-s-ravnom/

Light output 1



1 x LED

Nominal lamp power	30 W	LOR	100%
Lamp flux	3000 lm	Total flux	3000 lm
Luminous efficacy	100 lm/W	Total power	30 W
CCT	4000 K		
CRI	80		

Mounting mode

Ceiling recessed

Shape and measurements

Length: 23.62 in

Width: 23.62 in

Height: 2.76 in

Adjustability

Fixed

Electric

System power: 30 W

Protection

IP: 40

IK: 02