Product data sheet


EASYLINE_NEMESIS_TWIN_BLACK_111W_NEUTRAL_L2160MM
980121303_
PETRIDIS



IP 20

EASYLINE NEMESIS TWIN is an ideal solution for small showcases, homes, rest areas, museums, hotels, exhibition halls and generally for many decorative and architectural projects. Available in Wide light distribution can be the perfect tool for wide range of applications. Technical Features - Aluminium body, painted electrostatically in selected colour. - Reflector in black, white or transparent colour. - Pure light without IR/UV radiation. - Low glare (UGR< 19). - Efficient thermal management. - Operation life: 50,000 hours with efficiency > 80% of the initial luminous flux (L80B10). - Connection for operation with constant current. Upon Request - Connection for emergency lighting system, for one or three hours.

Light output 1



1 x LED

Nominal lamp power	111 W	LOR	67%
Lamp flux	12360 lm	Total flux	8281 lm
Luminous efficacy	111 lm/W	Total power	111 W
CCT	4000 K		
CRI	90		

Mounting mode

Ceiling mounted

Shape and measurements

Length: 85.04 in
Width: 2.44 in
Height: 3.15 in

Adjustability

Fixed

Design

Material impression: Aluminum, Chrome, Plastic

Electric

System power: 111 W
Controller: Dimmable 1..10V, DALI
Suitable for feed-through wiring
Appliance Class: I

Protection

IP: 20
Designation labels: CE