Product data sheet


59 PENDO LED ROPE-SUPPORTED LIGHT FITTING
59 1601 SL (59001 0500)
SCHUCH



IP 66 IK 10

LED rope-supported light fitting, PENDO, 17 W, 2980 lm, 175 lm/W, Class II, IP66, symmetrical wide beam, 4000 K, CRI≥ 70, Ta -40 °C/+25 °C, L90>100000 h (@ Ta max), Pane Safety glass clear, Closure Stainless steel V4A, Housing Die-cast aluminium, Colour as required. LED rope-supported light fitting of the GreenLine series with outstanding sustainable product design. Consisting of powder-coated die-cast aluminium housing, two-part. Upper part with bracket, adjustable inclination, cable entry and pressure compensation system. Lower part with LED modules, highly-efficient optics, frameless safety glass pane and ECG, hinged and detachable. Isolating plug connection and strain relief in junction box between upper and lower part, hinged and toolless accessible. Zhaga LED modules with highly efficient optics, direct beam, Multi-Layer Technology. ECG with high surge protection, overload and short circuit protection. Rope mounting with stainless steel bracket, rotatable (360°) and tiltable (15°) for ropes Ø 6-12mm. Resource-saving and environmentally friendly thanks to interchangeability of components (no disposable light fitting). Length 450,00 mm, Width/Diameter 350,00 mm, Height 212,00 mm, Net weight 6,60 kg.

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	17 W	CRI	70
Total flux	2980 lm	LOR	100%
Luminous efficacy	175 lm/W	ULOR	7%
		Total power	17 W

Mounting mode

Pendant, Contact rail

Shape and measurements

Length: 17.72 in
Width: 13.78 in
Height: 8.35 in

Adjustability

Fixed

Electric

System power: 17 W
Appliance Class: I

Protection

IP: 66
IK: 10
Designation labels: CE