Product data sheet

LD34 13.2W 350MA WB
LD34-C1-75-900-350-WB
LIGHTGRAPHIX



IP 67 IK 08

LD34 Recessed linear wall grazer. IP67. Constant Current 13.2W 350mA 48° Wide beam. The LD34 is a low glare, shallow recessed, in-ground, linear wall grazer which offers outstanding continuous wall washing capabilities for interior and exterior projects. It features a fixed 2.5° tilt, integral glare control options and individual cowls over each LED to ensure low glare from the viewer's perspective. Multiple colour temperatures and beam angles are available, as well as accessories including an optional frosted diffusion filter to illuminate even the lowest parts of the wall. With multiple set lengths and a compact design, this high-power solution will integrate into harsh environments ensuring long lasting reliability, excellent thermal and light output performance.

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	13.2 W	CRI	93
Total flux	1024 lm	LOR	100%
Luminous efficacy	78 lm/W	Total power	13.2 W

Mounting mode

Floor recessed

Shape and measurements

Length: 36.14 in
Width: 2.64 in
Height: 1.97 in

Adjustability

Fixed

Design

Material impression: Glass, Gloss, Matt, Stainless steel
Color of housing: Black, White, Anthracite / graphite, Silver gray

Electric

System power: 13.2 W
Controller: Dimmable 0..10V, Dimmable 1..10V, DMX, DALI
Appliance Class: III

Protection

IP: 67
IK: 08
Designation labels: CE

Other operating numbers

Ambient temperature range: -4...113°F