


Product data sheet

K-3 89 MR16
1027030X
MODULAR




Decorative simplicity Every project needs a basic spotlight for general lighting. K is our suggestion for those who like to keep things simple. Available with a diameter of 80 or 89 mm, a flat or sloping edge and in aluminium or with a white or black structure, K integrates easily into any room. Choose the directional model for a greater interplay of light.

Light output 1




1 x Halogen low voltage lamp without reflector

Nominal lamp power	45 W	LOR	100%
Lamp flux	625 lm	Total flux	623 lm
Luminous efficacy	12 lm/W	Total power	50 W
CCT	2800 K		
CRI	100		




1 x Halogen low voltage lamp without reflector

Nominal lamp power	45 W	LOR	100%
Lamp flux	830 lm	Total flux	830 lm
Luminous efficacy	17 lm/W	Total power	50 W
CCT	2800 K		
CRI	100		



1 x Halogen low voltage lamp without reflector

Nominal lamp power	45 W	LOR	100%
Lamp flux	830 lm	Total flux	829 lm
Luminous efficacy	17 lm/W	Total power	50 W
CCT	2800 K		
CRI	100		



1 x Halogen low voltage lamp without reflector

Nominal lamp power	45 W	LOR	100%
Lamp flux	830 lm	Total flux	829 lm
Luminous efficacy	17 lm/W	Total power	50 W
CCT	2800 K		
CRI	100		

Mounting mode

Ceiling recessed

Shape and measurements

Height: 0.39 in
Diameter: 3.54 in

Adjustability

Rotatable

Electric

System power: 50 W

Protection

IP: 20