


Product data sheet

OUTDOOR LIGHTING
V1-S1-70287-40L32-6507550 URAN 2.0 ROAD 75W 5000K
VARTON



Functional luminaire for outdoor lighting. High light output. Aluminum profile housing. Application: roads, outdoor industry, security zones. Installation: side-entry mounted (Ø40mm-48mm). Suitable for top end size, mm: 48 Impact resistance: IK01 Rated ambient temperature according to IEC62722-2-1, °C: -40...40 Protection class: I AC frequency, Hz: 50 Ingress protection (IP): IP65 Nominal voltage, V: 220...230 <https://www.varton.ru/products/ulichnoe-osveshchenie/uran-2-0/uran-2-0-road-dlya-dorogi/svetodiodnyy-konsolnyy-svetilnik-varton-ulichnyy-uran-2-0-road-75-vt-5000-k/>

Light output 1



1 x LED			
Nominal lamp power	75 W	LOR	100%
Lamp flux	11250 lm	Total flux	11250 lm
Luminous efficacy	150 lm/W	Total power	75 W
CCT	5000 K		
CRI	70		

Mounting mode

Pole integrated

Shape and measurements

Length: 13.74 in
Width: 8.03 in
Height: 3.23 in

Adjustability

Fixed

Electric

System power: 75 W

Protection

IP: 65
IK: 01