Product data sheet

LOG OUT HL T16 1X35/49/80W PMMA
528-94180
MOLTO LUCE



IP 20

Log Out T16, Einzelhängeleuchte; kantiges, geradliniges Aluminium Strangpressprofil; alu eloxierte Oberfläche, Abdeckung aus hochwertigem, flachem „BlendOpal"-Polycarbonat, für schattenfreie, homogene Lichtverteilung; werkzeugloses befestigen der Abdeckung und höhenverstellbare Seilaufhängung, inkl. Endkappen; Anschlussfertig, transparente Einspeisung 3x1mm²; 1x 35/49/80W T16 G5, 230V, Multiwatt EVG IP20;

Light output 1



1 x Fluorescent lamp tubular T5

Nominal lamp power	80 W	Socket	G5
Lamp flux	6150 lm	LOR	33%
Luminous efficacy	25 lm/W	Total flux	2016 lm
CCT	3000 K	Total power	80 W
CRI	85		



1 x Fluorescent lamp tubular T5

Nominal lamp power	49 W	Socket	G5
Lamp flux	4300 lm	LOR	33%
Luminous efficacy	18 lm/W	Total flux	1410 lm
CCT	3000 K	Total power	80 W
CRI	85		



1 x Fluorescent lamp tubular T5

Nominal lamp power	35 W	Socket	G5
Lamp flux	3300 lm	LOR	33%
Luminous efficacy	14 lm/W	Total flux	1082 lm
CCT	3000 K	Total power	80 W
CRI	85		

Mounting mode

Pendant

Electric

System power: 80 W
Appliance Class: I

Shape and measurements

Length: 58.23 in

Width: 2.36 in

Height: 3.54 in

Adjustability

Height adjustable

Protection

IP: 20