

Product data sheet


MILOS M AE 3000K 91 W 530 MA
SIMON LIGHTING



IP
65

SIMON Milos M Óptica AE 3000K 91 W 530 mA. Características técnicas: IP66 CRI>70. Acabado Dgclas. 11'5 kg Certificaciones: 2006/95/CE - Directiva Baja Tensión. 2004/108/CE - Directiva CEM. UNE-EN 60598: 2005 Luminarias. UNE-EN 62031: 2009 Módulos LED para alumbrado general. Requisitos de seguridad. UNE-EN 61347-2-13: 2007 Dispositivos de control de lámpara. UNE-EN 55015:2007 Límites y métodos de medida de las características relativas a la perturbación radioeléctrica de los equipos de iluminación y similares. UNE-EN 61547 Equipos para alumbrado de uso general. Requisitos de inmunidad - CEM. UNE-EN 61000-3-2 Compatibilidad electromagnética (CEM). UNE-EN 61000-3-3 Compatibilidad electromagnética (CEM).

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	91 W	CRI	80
Total flux	12260 lm	LOR	100%
Luminous efficacy	135 lm/W	Total power	91 W

Mounting mode

Ceiling mounted, Pole top mounted

Electric

System power: 91 W

Shape and measurements

Length: 19.09 in
Width: 16.54 in
Height: 5.51 in

Protection

IP: 65

Adjustability

Rotatable, Tilttable