
Product data sheet

MO SLIM 1.2FT 1600/840 S
63932
TREVOS



suspended indoor light fitting with accessories for various installation configurations either separately or in groups; the light fitting does not include end caps, couplers or suspender. Must be ordered separately; opal diffuser made of highly permeable, translucent polycarbonate; ON/OFF electronic driver (AC, DC on demand); Body: aluminium profile, aluminium white colour (RAL 9006); Diffuser: translucent polycarbonate (PC), UV stable, impact resistant; Reflector: steel sheet, white (RAL 9003); Connection: 2x screwless, five-pole terminal block, three-phase interconnection; Power: 10,5 W; Luminaire flux: 1400 lm; Lifetime: L90/B10; 50000 hours; Impact strength: IK08; Ambient temperature: -25|35 °C; Weight: 1,7 kg;

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	10.5 W	CRI	80
Total flux	1630 lm	LOR	100%
Luminous efficacy	155 lm/W	ULOR	4%
		Total power	10.5 W

Mounting mode

Pendant, Ceiling mounted

Shape and measurements

Length: 22.44 in
Width: 4.41 in
Height: 2.56 in

Adjustability

Fixed

Design

Color of housing: Silver gray, White
Designer: TREVOS

Electric

System power: 10.5 W
Ballast: ECG
Appliance Class: I

Protection

IK: 08
Designation labels: CE

Other operating numbers

Ambient temperature range: -13...95°F