
Product data sheet


RUBIN CLEAN LED 8800/800 MICRO-PRM SH E IP65 34 830/BLUE / 620X620MM TWO CIRCUIT
19.4067.3551.34
LUXIONA



IP 65 IK 08

Indoor luminaire. Assembly: surface mounted on ceiling. The body material is steel sheet. Colour - RAL 9016 (white). Dimensions: 620 x 620 x 78 mm. Diffuser: Micro-PRM SH (micro-prismatic diffuser PMMA with hardened glass). The efficiency of the optical system is 73,30%. Beam angle: (C0-C180) / (C90-C270) - 89° / 89°. Light source type: LED. Colour temperature – 3000 K/blue colour. SDCM=3. CRI>80. Lifetime of LED sources: 60000 h L80/B10. Luminaire luminous flux: 6511/918 lm. Power of luminaire: 48,8/17 W. Luminaire's light efficiency: 133,4/54 lm/W. Driver: standard on/off (E). Voltage 220..240 V, 50..60 Hz. Power factor cosφ: >0,95. Circuit load capacity: 7 (B10), 12 (B16), 12 (C10), 19 (C16). Operating temperature range: 5 ÷ 30° C. Protection degree: IP65. Impact resistant: IK08. Protection against electric shock: I. Photobiological risk class (IEC/EN 62471): RG0.

Light output 1



4 x LED

Nominal lamp power	12.2 W	LOR	52%
Lamp flux	2221 lm	Total flux	4658 lm
Luminous efficacy	182 lm/W	Total power	48.8 W
CCT	3000 K		
CRI	80		

Mounting mode

Ceiling mounted

Shape and measurements

Length: 24.41 in
Width: 24.41 in
Height: 3.07 in

Adjustability

Fixed

Design

Color of housing: White

Electric

System power: 48.8 W
Appliance Class: I

Protection

IP: 65
IK: 08

Other operating numbers

Ambient temperature range: 41...86°F