Product data sheet

LP CIRCLE SEMI RECESSED Ø450 WHITE LED 3000K 25W 5742583589

LOUIS POULSEN








LP Circle Semi Recessed Design: Mikkel Beedholm/KHR arkitekter Concept: The fixture emits diffuse light via a high-efficiency acrylic diffuser. The diffuser, which is encircled by a voluminous coloured or white ring, is hidden when viewed from low angles. Angling the inner side of the ring 5° creates a comfortable and decorative graduation of the light from the diffuser. With two diameters and four different installation options, the lights series can be used for a wide range of applications. Finish: White, Black, Pale Petroleum or Yellow. Powder coated. Material: Reflector: Extruded aluminium. Diffuser: Acrylic, frosted. Installation lock: Polyamide. Mounting: Ceiling thickness: 1–40 mm. Driver is a separate unit (supplied with fixture). Cut-out dimensions: Ø 260: Ø 248mm, Ø 450: Ø 438mm. Looping: Approved, max 5x1.5mm2. Weight: Min: 2.4 kg Max: 5.0 kg Class: Ingress protection IP20. Electric shock protection I.

Light output 1 (integrated)



| Lamp type | LED | CCT | 3000 K |
|--------------------|----------|-------------|--------|
| Nominal lamp power | 25 W | CRI | 90 |
| Total flux | 2706 lm | LOR | 100% |
| Luminous efficacy | 108 lm/W | Total power | 25 W |

Mounting mode

Ceiling recessed

Shape and measurements

Length: 17.95 in Width: 17.95 in Height: 4.06 in

Adjustability

Fixed

Electric

System power: 25 W

Protection

IP: 20