
Product data sheet

INNOVA 1.4FT PC 6400/840 2X5P
31549
TREVOS



fully automated and comprehensive inspection of functionality and tightness during production, venting membrane prevents the creation of negative pressure or condensation; variable suspension spacing ranging from 420 - 700 mm; enable the light to be installed onto suspension fittings left over from previous lighting; basic beam angle, optimal mounting height of up to 6 m; ON/OFF electronic driver (AC, DC on demand); external terminal box for connecting a power lead - plug&play system; Body: grey PC (high mechanical resistance, UV stability, RAL 7035); Diffuser: translucent PC (high mechanical resistance, UV stability); Reflector: steel sheet, white (RAL 9003); Connection: external, 5-pole, 1.5 mm2 conductor cross-section (2.5 mm2 available on demand); Power: 38,5 W; Luminaire flux: 6110 lm; Lifetime: L90/B10; 50000 hours; Impact strength: IK10; Ambient temperature: -25|45 °C; Weight: 1,7 kg;

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	38.5 W	CRI	80
Total flux	6500 lm	LOR	100%
Luminous efficacy	169 lm/W	ULOR	4%
		Total power	38.5 W

Mounting mode

Ceiling mounted

Shape and measurements

Length: 46.26 in
Width: 3.54 in
Height: 3.94 in

Adjustability

Fixed

Design

Material impression: Plastic
Color of housing: Silver gray, White
Designer: TREVOS

Electric

System power: 38.5 W
Ballast: ECG
Appliance Class: I

Protection

IP: 66
IK: 10
Designation labels: CE, ENEC

Other operating numbers

Ambient temperature range: -13...113°F