

Product data sheet


FOGO S CME 4000K 54 W 530 MA
SIMON LIGHTING



IP
65

SIMON Fogo S Óptica CME 4000K 54 W 530 mA. Características técnicas: IP66 CRI>70. Acabado GYTECH. 12,5 kg Certificaciones: 2006/95/CE - Directiva Baja Tensión. 2004/108/CE - Directiva CEM. UNE-EN 60598: 2005 Luminarias. UNE-EN 62031: 2009 Módulos LED para alumbrado general. Requisitos de seguridad. UNE-EN 61347-2-13: 2007 Dispositivos de control de lámpara. UNE-EN 55015:2007 Límites y métodos de medida de las características relativas a la perturbación radioeléctrica de los equipos de iluminación y similares. UNE-EN 61547 Equipos para alumbrado de uso general. Requisitos de inmunidad - CEM. UNE-EN 61000-3-2 Compatibilidad electromagnética (CEM). UNE-EN 61000-3-3 Compatibilidad electromagnética (CEM).

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	54 W	CRI	80
Total flux	7890 lm	LOR	100%
Luminous efficacy	146 lm/W	Total power	54 W

Mounting mode

Ceiling mounted, Pole top mounted

Shape and measurements

Height: 15.59 in
Diameter: 12.95 in

Adjustability

Rotatable, Tilttable

Electric

System power: 54 W

Protection

IP: 65