



Product data sheet

AMP L LT 6400-840 PC NB IVG
42929118
ZUMTOBEL



LED Moisture-proof diffuser luminaire with IP66 protection rating and drip-edge effect for minimising dirt and collection of dust for maximum hygienic requirements. Total power: 41.2 W, with dimmable constant current built-in control gear for LED suitable for industrial applications in tough environments such as cold warehouses or factories with high ambient temperatures; patented InvisiClick for clipless mounting and opening of the cover. Cover and basic diffuser made of impact-resistant polycarbonate, temperature- and UV-resistant, made as a single injection-moulded piece. LED service life lasts 50000 h before luminous flux is reduced to 90% of the initial value. Chromaticity tolerance (initial MacAdam): 3. Luminaire luminous flux: 6390 lm, Luminaire efficacy: 155 lm/W. Colour rendering Ra > 80, colour temperature 4000 K. Luminaire with symmetric narrow light distribution (narrow beam). Mounting via V2A standard spring clips to ceilings, walls or trunking. 5-pole connector terminal. ambient temperature: -40°C to +44°C. Approved for indoor use or use in outdoor areas protected by a roof with vertical or horizontal wall mounting (see installation instructions). Luminaire wired with halogen-free leads and contains no silicone. Complies with International Food Standard specifications. Designed for BESA box. Degree of protection: IP66, class of protection: SC1, 850°C glow-wire tested, Impact strength: IK08, Dimensions: 1600 x 90 x 92 mm; weight: 3.41 kg.

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	41.2 W	CRI	80
Total flux	6390 lm	LOR	100%
Luminous efficacy	155 lm/W	ULOR	6%
		Total power	41.2 W

Mounting mode

Ceiling mounted

Shape and measurements

Length: 62.99 in
Width: 3.54 in
Height: 3.62 in
Weight: 3.4 kg

Design

Material impression: Plastic

Electric

System power: 41.2 W
Voltage: 220-240 V AC
Appliance Class: I

Protection

IP: 66
IK: 08
Designation labels: CE