



Product data sheet

RECESSED CEILING LUMINAIRE SLASH 2 HPE (HIGH PERFORMANCE EF
2006.3966 - SLASH2 CR1198 LED1940-840 DIR ELOX DALI
REGENT



Recessed ceiling luminaire Slash 2 HPE (High Performance Efficiency), with LED, system power: 19 W, standby power 0.5 W, luminous flux of luminaire 1940 lm, colour rendering index CRI > 80, colour temperature 4000 K, neutral white, colour tolerances SDCM 3, lifetime LED L80 75'000 h, photobiological safety: the luminaire poses no danger (RG0), 230 V, direct light emission, luminaire profile in aluminium natural-colour anodised with ceiling trim, diffuser in polycarbonate (PC), APD (Added Performance Diffuser), OpalLed, 1 integral control gear, DALI, Regent certified MINERGIE®-Modul luminaires S.A.F.E. 2019 (Re-0288), luminaire complies with the strict requirements for Minergie-certified luminaires protection class I, ingress protection IP20, glow wire test 850 °C, impact strength: IK 08 this product contains a light source of energy efficiency class B and EPREL registration number: 1249140 L = 1198 mm, B = 61 mm, EL = 1187 mm, EB = 48 mm, ET = 70 mm

Light output 1



1 x LED			
Nominal lamp power	20 W	LOR	100%
Lamp flux	1940 lm	Total flux	1940 lm
Luminous efficacy	97 lm/W	Total power	19 W
CCT	4000 K		
CRI	80		

Mounting mode

Ceiling recessed

Shape and measurements

Length: 47.17 in

Width: 2.40 in

Height: 2.76 in

Weight: 4.386 kg

Adjustability

Fixed

Design

Color of housing: Silver gray

Electric

System power: 19 W

Appliance Class: I

Protection

IP: 20

IK: 08