


# Product data sheet

MELRIE  
485722  
FLOS



• Outdoor luminaire for surface installation on wall • Configuration: polycarbonate structure and die-cast aluminium cover, diecast aluminium base (MaxiMelrie) EN AB-47100 alloy (low copper content). • Double layer coating for high resistance to corrosion: The low copper Aluminium alloy is painted with a double coat using powders which are complaint with QUALICOAT standards: a first layer of epoxy powder (with excellent chemical and mechanical resistance) and a second finishing layer of polyester powder (resistant to UV rays and atmospheric agents).The entire painting process of the aluminium fitting starts from components which have been sand-blasted in advance to make the surface more porous and increase the adherence of the paint. Ares effects alkaline and acid washing to clean the surfaces completely, then rinses with demineralised water to remove any residue particles, subsequently a chemical conversion treatment is done to protect against rusting. • Expanded silicone gaskets.

## Light output 1



1 x Compact fluorescent lamp			
Nominal lamp power	13 W	Socket	G24Q-1
Lamp flux	900 lm	LOR	32%
Luminous efficacy	22 lm/W	ULOR	16%
CCT	3000 K	Total flux	284 lm
CRI	84	Total power	13 W

## Mounting mode

Wall mounted

## Shape and measurements

Length: 7.87 in  
Width: 3.94 in  
Height: 4.33 in

## Adjustability

Fixed

## Electric

System power: 13 W

Appliance Class: II

## Protection

IP: 65

IK: 09