


# Product data sheet

MOD\*S L45  
MOD SLIM  
DEXTRA



MOD Slim- 600x600, IP40, IK08 Recessed luminaire, white powder coated steel body, high transmission polycarbonate diffuser. Replace \* with P for Pull-up or R for Lay-in. Options: E3 - Emergency control gear (466 lumens output) ST3 - Emergency Selftest AT3 - Emergency Autotest S - Switch Dimming D - Digital Dimming (DSI) A - Digital Addressable Lighting Interface (DALI) C - Bi-Level Dimming (Corridor Function)\* H - High Frequency Dimming (Analogue 1-10v) WT - White Tunable, Lumen outputs vary R44 - Daylight regulating and Occupancy Sensor RAS - Reacta Air Wireless occupancy and daylight dimming RLS - Reacta-Link Wireless Presence & Daylight Sensor RCS - Reacta-Control Wireless, Presence IP44 - IP44 rating (from below) 4PM - 4 Pole panel mount 6PM - 6 Pole panel mount MODRS TETHER KIT - Secondary fix single drop MODRS TETHER KIT TWIN- Secondary fix twin drop

## Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	26.5 W	CRI	80
Total flux	3484 lm	LOR	100%
Luminous efficacy	131 lm/W	ULOR	4%
		Total power	26.5 W

## Mounting mode

Ceiling recessed

## Shape and measurements

Length: 23.62 in

Width: 23.62 in

Height: 2.68 in

## Adjustability

Fixed

## Electric

System power: 26.5 W

Ballast: ECG

## Protection

IP: 20

IK: 08

Designation labels: CE