


# Product data sheet

KAP 145  
03.4481.GL/QT-12/75W/100W  
FLOS




Luminaire with embedded installations on ceilings for halogen lamps and metal halide. The Easy Kap version, incorporates body injected in zamak with liquid paint finish and outer diameter of 105mm with opal glass diffuser. Pre-frame instalation not necessary. The Kap version incorporates body injected in aluminium with liquid paint finish. It is available in two sizes: 105mm and 145mm, always in No Trim installation. Main view made of anodized gloss aluminium with diffuser element made in borosilicate glass. Lampholders with heatsink element in injected aluminium and embedment ring of the optical body in thermoplastic material. Finishings: white (B1), matt gold (GL), blue (BU) and black (74).

## Light output 1



### 1 x Halogen low voltage lamp without reflector

Nominal lamp power	100 W	Socket	Gy6.35
Lamp flux	2200 lm	LOR	39%
Luminous efficacy	8 lm/W	Total flux	848 lm
CCT	3000 K	Total power	100 W
CRI	99		



### 1 x Halogen low voltage lamp without reflector

Nominal lamp power	75 W	Socket	Gy6.35
Lamp flux	1575 lm	LOR	39%
Luminous efficacy	8 lm/W	Total flux	607 lm
CCT	3000 K	Total power	75 W
CRI	99		

## Mounting mode

Ceiling recessed

## Shape and measurements

Height: 7.87 in  
Diameter: 5.71 in

## Adjustability

Fixed

## Electric

System power: 75-100 W  
Appliance Class: III

## Protection

IP: 43