

Product data sheet

TENUO
671947.004.07
RZB




IP
40

IK
03

Series: TENUO Luminaire for escape route identification. Housing: anodised aluminium, silver. Display panel: patented MicroLens technology and legend on both sides. Electronic ballast included. Self-contained system with automatic self-test and feedback via DALI bus, only to RZB DALI monitoring system. Please indicate legend number when placing your order! Colour: silver, matt (approx. RAL 9006) Length: 420 mm Width: 55 mm Height: 202 mm Cut-out length: 400 mm Cut-out width: 40 mm Recess height: 90 mm Luminaire: recess height: 60 mm Weight: 2.14 kg Operating mode: maintained power mode Viewing Distance: 30 m Duration time: 3 h Lamp: LED Socket: without socket Colour temperature: 5700K Colour rendering index (CRI): 80 System power: 7.1 W System power, emergency: - Control gear: EB Protection class: I Type of protection: IP 40

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	0.01 W	CRI	80
Total flux	1 lm	LOR	100%
Luminous efficacy	100 lm/W	ULOR	35%
		Total power	0.01 W

Mounting mode

Ceiling recessed

Electric

System power: 0.01 W

Shape and measurements

Length: 2.17 in
Width: 16.54 in
Height: 7.95 in

Protection

IP: 40
IK: 03

Adjustability

Fixed

Design

Color of housing: Silver gray