


Product data sheet

LED FLOODLIGHT 30W, COLD WHITE, BLACK, IP65
113362
ISOLED



LED floodlight 30W, cool white, black, IP65, 2-year guarantee, for indoor and outdoor use, 2400 lm, 6500K, 70000 h useful life | Dimensioned power: 30 W | Effective power: 30 W | Energy efficiency class: F (EU 2019/2015) | Nominal Voltage: 220 - 240 V AC | Material: die-cast aluminum | Surface color: Black | Protection class: IP65 | Allowable ambient Temperatures: -20° - 40° C | Beam angle: 120° fixed | Color temperature: 6500K | Color rendering index: 80 (Ra 1-8) | Luminous flux: 2400 lm | Suitable for indoor and outdoor use | Usable life: 70000 h (L80|B50) | Warranty: 2 years | Special features: Incl. 1 meter 3-pin connecting cable which can be easily removed from the sealed connection terminal on the back and the floodlight can be connected directly to an existing power supply line. | FABRICATION: ISOLED 113362

Light output 1



1 x LED			
Nominal lamp power	30 W	LOR	100%
Lamp flux	2400 lm	ULOR	3%
Luminous efficacy	80 lm/W	Total flux	2400 lm
CCT	6500 K	Total power	30 W
CRI	80		

Mounting mode

Wall mounted

Shape and measurements

Length: 7.48 in
Width: 2.40 in
Height: 7.48 in

Adjustability

Tiltable

Design

Material impression: Aluminum
Color of housing: Black

Electric

System power: 30 W
Ballast: ECG

Protection

IP: 65
Designation labels: CE

Other operating numbers

Ambient temperature range: -4...104°F