


Product data sheet

LEDFIT S 45W A/S CL1 L840
96628332
THORN LIGHTING



A simple, ultra lightweight, small LED area floodlight with true asymmetric optic. Integral fixed output control gear. Class I electrical, IP66, Impact strength: IK07. Body: die-cast aluminium painted light grey (RAL 9006). Stirrup: galvanised steel. Visor: polycarbonate with external surface powder coated light grey (RAL 9006). Pre-wired with 0.6m cable. Stirrup can be fixed by one M10 and/or two M8 fixation points, it is reversible allowing different mounting positions. Complete with 4000K LED. Dimensions: 181 x 236 x 48 mm Total power: 45 W Luminaire luminous flux: 4500 lm Luminaire efficacy: 100 lm/W weight: 1.7 kg

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	45 W	CRI	80
Total flux	4500 lm	LOR	100%
Luminous efficacy	100 lm/W	Total power	45 W

Mounting mode

Ceiling mounted

Shape and measurements

Length: 7.13 in
Width: 9.29 in
Height: 1.89 in
Weight: 1.7 kg

Design

Material impression: Aluminum
Color of housing: Silver gray

Electric

System power: 45 W
Voltage: 220-240 V AC
Appliance Class: I

Protection

IP: 66
IK: 07
Designation labels: CE, ENEC