Product data sheet

POLE MOUNTED LUNINAIRE VARESE 3000K 10.12220.0VXXX

HESS







Convex luminaire canopy made of aluminium. Luminaire enclosure made of PMMA, clear. Diameter 200mm. Cylindrical luminaire body made of cast aluminium, elegantly tapering towards the pole. Holder for poles with 76.1 mm.

Light output 1



I X LED	
Nominal lamp power	20 W
Lamp flux	2299 lm
Luminous efficacy	115 lm/W
CCT	3000 k
CRI	80

L	LOR	100%
٦	otal flux	2299 lm
٦	otal power	20 W



I X LED	
Nominal lamp power	20 W
Lamp flux	2317 lm
Luminous efficacy	116 lm/W
CCT	3000 K
CRI	80
	3000 K 80

1 V I ED

LOR	100%
Total flux	2317 lm
Total power	20 W



1 x LED			
Nominal lamp power	20 W	LOR	100%
Lamp flux	2332 lm	Total flux	2332 lm
Luminous efficacy	117 lm/W	Total power	20 W
CCT	3000 K		
CRI	80		



1 x LED

Nominal lamp power	20 W	LOR	100%
Lamp flux	2368 lm	Total flux	2368 lm
Luminous efficacy	118 lm/W	Total power	20 W
CCT	3000 K		
CRI	80		



1 x LED

I X LLD			
Nominal lamp power	28 W	LOR	100%
Lamp flux	3072 lm	Total flux	3072 lm
Luminous efficacy	110 lm/W	Total power	28 W
CCT	3000 K		
CRI	80		



1 x LED

Nominal lamp power	28 W	LOR	100%
Lamp flux	3082 lm	Total flux	3082 lm
Luminous efficacy	110 lm/W	Total power	28 W
CCT	3000 K		
CRI	80		



1 x LED

I X LLD			
Nominal lamp power	28 W	LOR	100%
Lamp flux	3147 lm	Total flux	3147 lm
Luminous efficacy	112 lm/W	Total power	28 W
CCT	3000 K		
CRI	80		



1 x LED

Nominal lamp power	28 W	LOR	100%
Lamp flux	3102 lm	Total flux	3102 lm
Luminous efficacy	111 lm/W	Total power	28 W
CCT	3000 K		
CRI	80		



1 x LED

Nominal lamp power	28 W	LOR	100%
Lamp flux	3057 lm	Total flux	3057 lm
Luminous efficacy	109 lm/W	Total power	28 W
CCT	3000 K		
CRI	80		



1 x LED

Nominal lamp power	20 W	LOR	100%
Lamp flux	2310 lm	Total flux	2310 lm
Luminous efficacy	116 lm/W	Total power	20 W
CCT	3000 K		
CRI	80		

Mounting mode

Pole top mounted

Shape and measurements

Length: 7.95 in Width: 7.95 in Height: 33.06 in

Adjustability

Fixed

Electric

System power: 20-28 W

Protection

IP: 65