Product data sheet

MARVIK 4 WALL SURFACE LUMINAIRES MV-30031-VW-W40

LIGMAN









- Lamp COB - CRI Ra > 80 - MacAdam Ellipse 3 SDCM - Colour 3000K and 4000K - Die-cast aluminium housing and frame pre-treated before powder coating ensuring high corrosion resistance - Single cable entry - Stainless steel fasteners in grade 316 - Durable silicone rubber gasket - High-efficiency optical reflector - Clear toughened glass - Integral control gear

Light output 1 (integrated)



| Lamp type | LED | CCT | 4032 K |
|--------------------|---------|-------------|--------|
| Nominal lamp power | 11 W | CRI | 80 |
| Total flux | 935 lm | LOR | 100% |
| Luminous efficacy | 85 lm/W | Total power | 11 W |

Light output 2 (integrated)



| Lamp type | LED | CCT | 4032 K |
|--------------------|---------|-------------|--------|
| Nominal lamp power | 11 W | CRI | 80 |
| Total flux | 935 lm | LOR | 100% |
| Luminous efficacy | 85 lm/W | Total power | 11 W |

Mounting mode

Wall mounted

Shape and measurements

Height: 7.87 in Diameter: 4.13 in Weight: 1.7 kg

Adjustability

Fixed

Glare protection

Glare protection: UGR < 19

Electric

System power: 22 W Voltage: 230 V AC Ballast: ECG

Controller: Dimmable 1..10V, DALI

Appliance Class: I

Design

Color of housing: Black, White, Silver gray

Protection

IP: 65

IK: 08

Surface temperature: 40°C