Product data sheet

RIBBON GO 5 OB DC 4W 865 140 5M IP20
DL26PLN101258
TRAXON



IP 17

Product Details The Traxon Ribbon Go 5 family are flexible LED ribbons, which are reliable and multi-optional with comprehensive features, available in both indoor and outdoor versions, making them the perfect solution for a variety of applications, including linear, flexible, creative ambient projects, curved lighting and freeform applications. Advantages & Benefits Features Available with Open Beam IP20, Flat IP66, Top-bending IP67, and Side-bending IP67 versions Up to 4000lm/m Ra80/90 White, Dynamic White, RGB, and RGBW options ON/OFF, DALI, PWM, 0-10V, 1-10V, DMX2PWM Dimmer, Radio Frequency Lumen Maintenance L70@25° – 50,000 Hrs Colour Options 2700K 3000K 3500K 4000K 5000K 6500K RGB RGBW (White = 4000K) Dynamic White 2700K-6500K Beam Options 120° IP Options Open Beam IP20 Flat IP66 Top IP67 Side IP67 Do you need more information? For further information like local representatives or product documentation, please contact us.

Light output 1



140 x LED

Nominal lamp power	0.029 W	LOR	100%
Lamp flux	4 lm	Total flux	560 lm
Luminous efficacy	153 lm/W	Total power	4.12 W
CCT	6500 K		
CRI	80		

Mounting mode

Ceiling mounted

Shape and measurements

Length: 0.63 in
Width: 39.37 in
Height: 3.94 in

Adjustability

Fixed

Electric

System power: 4.12 W

Protection

IP: 17