


Product data sheet

LINEAR LIGHTING
V1-R0-00828-02OPD-4001040 X-LINE 0,50 M STAND-ALONE 10W 4000K DALI
VARTON




IP
40

IK
01

• Extruded aluminum luminaire • Standalone Application • Retail spaces • Administrative facilities Installation • Surface-mounted • Suspended
Input voltage (AC, 50Hz), V: 176...264 AC frequency, Hz: 50 Flicker, %: 1 Climatic modification and category of placement: УХЛ4 Color rendering
index: 80-89 Protection class: I Mounting method: Pendant Ingress protection (IP): IP40 Radiation angle: Radiation angle, °: 100 Impact
resistance: IK01 Power factor: 0,9 https://www.varton.ru/products/lineynye-svetilniki-dlya-vnutrennego-osveshcheniya/x-line-odinochnye/x-line-0-50-m-odinochnye/cvetilnik-var-ton-x-line-0-5-m-10-vt-odinochnyy-podvesnoy-4000-k-507x63x100-mm-ip40-ral7045-seryy-mua_1/

Light output 1



1 x LED			
Nominal lamp power	10 W	LOR	100%
Lamp flux	1100 lm	Total flux	1100 lm
Luminous efficacy	110 lm/W	Total power	10 W
CCT	4000 K		
CRI	80		

Mounting mode

Pendant

Shape and measurements

Length: 19.96 in
Width: 2.48 in
Height: 3.94 in

Adjustability

Fixed

Electric

System power: 10 W

Protection

IP: 40
IK: 01