


# Product data sheet

LED DOWNLIGHT SERIES DLEL 6W 6500K  
DLEL-6T  
MPE



- Round shape - Recessed - mounted on ceiling or use additional SRDLE accessories for floating mounting - Driver is integrated inside the light.
- Size: Ø102 x 50 mm - Cut out: Ø90mm - Voltage: 100-240VAC - Power: 6W - Power Factor (PF): >0.5 - Luminance: 600 lm - Color Temperature (CCT): 6000-6500K - RA >80 High Color Rendering Index - Beam angle: 110° - Chip LED: SMD 2835 - Life Time: 30,000 hours - Instant Light: 0s
- European Standard CE - RoHS

## Light output 1



1 x LED			
Nominal lamp power	6 W	LOR	100%
Lamp flux	600 lm	Total flux	600 lm
Luminous efficacy	99 lm/W	Total power	6.06 W
CCT	6500 K		
CRI	82		

## Mounting mode

Ceiling recessed

## Shape and measurements

Length: 46.26 in  
Width: 3.86 in  
Height: 3.31 in

## Adjustability

Fixed

## Design

Material impression: Plastic  
Designer: TREVOS

## Glare protection

Glare protection: UGR < 19

## Electric

System power: 6.06 W  
Ballast: ECG

## Protection

IP: 20  
Designation labels: CE

## Other operating numbers

Ambient temperature range: -13...113°F