Product data sheet


AVN D2 18L35 WST BPSW CL2 N4M L730 CU
96261386
THORN LIGHTING



IP 66 IK 08

An elegant LED amenity lantern. Electronic, fixed output control gear. Light distribution: asymmetrical. Class II electrical, IP66, IK08. Base and arms: die-cast aluminium, powder coated dark sandy grey 900. Canopy: spun aluminium, powder coated dark sandy grey 900. Lampshield: metallised polycarbonate with copper. Diffuser: clear UV stabilised polycarbonate with anti glare prisms. Equipped with power reduction circuit, effective 3 hours before and 5 hours after a calculated midnight. It can be deactivated at installation with an easily accessible internal switch. Pre-wired with 4m H05-RNF cable. Complete with 3000K LED Dimensions: Ø596 x 732 mm Total power: 21 W Weight: 9 kg Scx: 0.134 m²

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	21 W	CRI	70
Total flux	1814 lm	LOR	100%
Luminous efficacy	86 lm/W	ULOR	5%
		Total power	21 W

Mounting mode

Pole top mounted

Shape and measurements

Height: 28.82 in
Diameter: 23.46 in
Weight: 9 kg

Design

Material impression: Aluminum

Electric

System power: 21 W
Voltage: 230 V AC
Appliance Class: II

Protection

IP: 66
IK: 08
Designation labels: CE