


Product data sheet

CIRCULUS BRUSHED STEEL 19W LED 3000K RA>80
5046297001
SG ARMATUREN



Round surface-mounted luminaire, wholly uniform light with attractive design, made of powder-coated aluminium, simple to mount by removing the back plate, which can be screwed on to all known ceiling outlets/electrical boxes, clips with option of additional looping, connectors between lamp and mounting plate, dimmable driver phase-dimming/DALI and sensor options. Both visible and hidden cabling possible. Light distribution Direct Light technic LED (not exchangeable) 19W 3000K Ra>80 SDCM 3 L80/B10 >50,000 hrs at Ta=25°C L70/B50 >100,000 hrs at Ta=25°C Control/Dimming Trailing edge dimming Protection Class I IP21 Energy and approvals A+ CE Materials and finish Housing: Steel Colour: Brushed steel Optics: PMMA Polymethylmethacrylat Mounting/Connection Surface, Indoor Screwless terminal block

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	19 W	CRI	80
Total flux	1340 lm	LOR	100%
Luminous efficacy	71 lm/W	Total power	19 W

Mounting mode

Ceiling mounted

Shape and measurements

Length: 14.17 in

Width: 14.17 in

Height: 1.77 in

Adjustability

Fixed

Electric

System power: 19 W

Appliance Class: I

Protection

IP: 21